

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)


PCT

(10) International Publication Number
WO 2005/014332 A1

- (51) International Patent Classification⁷: B60N 2/06.
2/20, 2/30
- (21) International Application Number: PCT/GB2004/002930
- (22) International Filing Date: 7 July 2004 (07.07.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0317103.0 22 July 2003 (22.07.2003) GB
- (71) Applicant (for all designated States except US): JOHN-
SON CONTROLS AUTOMOTIVE (UK) LTD
[GB/GB]; The Hamilton Centre, Widford Industrial
Estate, Chelmsford, Essex CM1 3BY (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): LEWIS, Ian [GB/GB];
Johnson Controls Automotive (UK) Ltd, The Hamilton
- (74) Agent: DEALTRY, Brian; Eric Potter Clarkson, Park
View House, 58 The Ropewalk, Nottingham NG1 5DD
(GB).
- (81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AI, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PI, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.
- (84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: VEHICLE SEAT SUPPORT STRUCTURE



(57) Abstract: A vehicle seat support structure (12) for mounting a vehicle seat (S) on a floor of a vehicle for selective movement between first and second positions, which are laterally spaced from one another relative to the vehicle, includes a plurality of links (20). Each of the links (20) is adapted to be pivotally connected at one end to the vehicle seat (S) and at its other end to the vehicle floor.



FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BE, BJ, CI, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*